

**AMENDMENT**

**In the Claims:**

Claims 1 to 47 (Canceled).

48.    **(CURRENTLY AMENDED)**       A method for configuring a medical carrier, the method comprising:  
          first providing an elongate body having at least one shared electrical conductor, wherein the shared electrical conductor carries data; and  
          electrically coupling at least two separately identifiable effectors to the at least one shared electrical conductor, wherein the at least two separately identifiable effectors are axially spaced apart along the length of the elongate body and each of the at least two separately identifiable effectors comprises:  
          a plurality of electrodes;  
          an identifiable microprocessor electrically coupled to the plurality of electrodes, wherein each electrode of the effector is individually addressable and wherein each effector is controlled by its microprocessor independent of other effector; and  
          configuring each effector by providing instructions to the microprocessor.

49.    (Original)       A method as in claim 48, wherein the providing step comprises providing the body coupled with a cardiac pacing lead.

50.    **(CURRENTLY AMENDED)**       A method as in claim 48, wherein the providing step comprises providing a body having ~~at least two~~ a second electrical conductors, each conductor disposed in a separate lumen along at least a portion of the body.

51.    (Canceled)

52. (Previously Presented) A method as in claim 48, wherein said elongate body is an implantable lead.

Claims 53 to 58 (Canceled).

59. (Original) A method as in claim 48, wherein at least one of the effectors comprises both a sensor and an actuator.

60. (Original) A method as in claim 59, wherein the sensor is selected from the group consisting of pressure sensors, volume sensors, dimension sensors, temperature or thermal sensors, oxygen or carbon dioxide sensors, electrical conductivity sensors, electrical potential sensors, pH sensors, chemical sensors, flow rate sensors, optical sensors, acoustic sensors, hematocrit sensors and viscosity sensors.

61. (Original) A method as in claim 59, wherein the actuator performs a function selected from the group consisting of providing an electrical current or voltage, setting an electrical potential, heating a substance or area, inducing a pressure change, releasing or capturing a material, emitting light, emitting sonic or ultrasound energy and emitting radiation.

Claims 62-64 (**CANCELED**).

65. (Original) A method as in claim 48, further comprising encapsulating at least a portion of the body and the mounted effectors with an encapsulating material.

66. (**CANCELED**).

67. (**CURRENTLY AMENDED**) An improved method for configuring a medical carrier of the type including a plurality of systems, wherein the improvement comprises:

first providing separately identifiable satellite units systems, wherein the units  
are axially spaced apart along the length of the carrier's body and wherein  
at least one unit system comprises:

at least two electrodes effectors on a surface of an elongate body; that  
each ~~comprise a transducer and~~  
an identifiable microprocessor comprising capable of handling instructions  
~~a chip comprising an analog to digital converter,~~

~~wherein said effectors are axially spaced apart along the length of the body;~~ and  
then electrically coupling each unit of said ~~at least two effectors~~ to one shared  
conductor through a surface penetration of ~~said surface of said~~ the body and  
wherein each effector surrounds its microprocessor.

68. (CURRENTLY AMENDED) A method as in claim 67, wherein  
each unit system comprises:

at least one sensor; and  
at least one actuator; ~~and~~  
~~an electronic circuit.~~

Claims 69 to 113 (Canceled).

114. (NEW) A method for configuring a medical carrier of the type  
including a plurality of satellite units, the method comprises:  
positioning at least two separately identifiable effectors along an elongate body,  
wherein each effector comprises:  
a microprocessor capable of handling instructions; and  
a plurality of electrodes that are axially positioned around the  
microprocessor and electrically coupled to the microprocessor  
and controlled thereby;

electrically coupling the microprocessor of each effector to a pair of shared  
conductors running the length of the elongated body, wherein the shared  
conductors carry power and data; and  
configuring each effector through instructions provided to the microprocessor  
using one conductor of the pair of shared conductors.